



DURAWEB

Whatever it takes

We do whatever it takes to help you operate more effectively. Our specialists will visit your facility to help you identify the printing blanket that will work with the other consumables of your operation and the required print job. Our technicians are former press operators who can help troubleshoot press problems even beyond printing blankets.

MAIN APPLICATION

Commercial Web

Vulcan Duraweb is available in 3/4-ply, (.067"/.077" +/- .001") thickness.



Standard



Vulcan Duraweb

 The product at a glance

PRINTING SURFACE COLOUR	Light Green
THICKNESS (mm)	.067" (1.71 mm)/ .077"(1.96 mm)
SURFACE ROUGHNESS (Ra micron)	0.6
INK COMPATIBILITY	Conventional
ELONGATION (%)	<0.9
TENSILE STRENGTHS (N/mm)	>60
AVERAGE LOAD VALUE N/cm ² @ 0,23 mm Indentation	250
PAPER FEEDING	Positive
WATER SOLVENT PROTECTED	Yes
ADDITIONAL INFORMATION	
PRODUCT'S HIGHLIGHT	Buffed surface allows for full solids and maximum release, excellent print quality, unique top fabric allows printing to the gap, extremely suitable for today's high speed webs.

Follow us:

www.trelleborg.com/printing

On Twitter: @printinginsight

Blogging at: printinginsightsblog.trelleborg.com

On LinkedIn at: www.linkedin.com/groups/Printing-insights

IF YOU WOULD LIKE TO SPEAK TO SOMEONE ABOUT THIS PRODUCT OR ANY OTHER VULCAN PRODUCT PLEASE CONTACT ONE OF OUR DEDICATED TEAM: printing@trelleborg.com